

**2012**  
**CANAAN FAIR ASPHALT SPEEDWAY**  
**SUPER STREET RULES**

**ATTENTION SUPER STREET COMPETITORS**

The Super Street Class is intended to provide and encourage stock car racing at an affordable price. The objective of this class is to provide affordable racing and to have fun. Efforts to “bend” or take advantage of “gray” area rules will not be tolerated! It is nearly impossible with all the different types of vehicles allowed in this class to provide a rulebook which will cover every possible situation that might occur. The Technical Inspector(s) are given discretion to use their judgment to interpret and make changes to these rules at any time should it be deemed necessary, to insure equal competition for all. Management reserves the right to impose weight penalties to any vehicle deemed hurting the competition.

**NEW RULES FOR 2012**

- 2. 8” GOODYEAR tire will be used for 2012 (same as late model) Tire purchasing limitations will set by cfs. American racer tire #704 will also be allowed to compete.**
- 1. Age limitations will be at the discretion of CFS and must meet CFS criteria to compete.**
- 33. one 5” mirror only will be allowed on drivers post**

**COMPETING MODELS:**

- 1. Any 1969 or newer, full bodies American made car is allowed.**
- 2. Bodies and frames may interchange.**

**BODIES:**

- 1. Steel, Aluminum or Fiberglass bodies allowed.**
- 2. Nose and tail covers may be aftermarket.**
- 3. Rear of car must be closed in.**
- 4. Metal rub rails or composite rub rails allowed. Ends must be flattened to contour of the body.**
- 5. There will be a 4” ride height rule. All ride heights will be checked after race on tech floor, No waiting for car to rise due to pull down shock ect. No adding air to tires. If a tire is flat or loosing air it will be to the discretion of tech to change the effected**

tire. All frame and body will be 4"

6. Ride height will be measured with driver seated in the car, measured on the tech shed floor at all times.
7. CFS Officials reserve the right to adjust this rule at any time due to racing damage.
8. Rear spoiler is to be clear lexan, and no taller than 10" regardless of angle. It will be measured from mounting surface to the top edge of the spoiler. 0" tolerance. It is to be mounted in the center of the body, and no wider than 60". The height is to be no higher than 45" from the CFS tech floor at its highest point. Side skirts and center bracing is allowed. Spoiler height will be checked with the driver in the car after the feature. The discretion of the tech department will be final.

### **FRAMES:**

1. Tube chassis's, Metric chassis's, 4 link Metric Chassis's, Leaf spring chassis's, Camaro clip with tube chassis's, or Metric chassis's with 3 point hitch are allowed, with various weight packages depending on style of chassis.
2. All chassis's must have steering boxes.
3. No rack and pinion types allowed.

### **WEIGHT RULES:**

2. All cars running World Product Inc. heads, part #12250 must add 50 lbs of weight to the base weight for their car.
3. All lead weight ballast MUST be painted white, be securely mounted and have competitors number on it.
4. The following weight rules are in effect, Weights are based of approved RPM, Butler McMaster sealed Crate motor 602 Option:

**METRIC WITH OEM 4 POINT :** Minimum total weight is 2,850 lbs. 57% Left

**CAMARO CLIP WITH A TUBE / TREE POINT or METRIC CHASSIS WITH 3 POINT HITCH:** Minimum total weight is 2,900 lbs. 56% Left

**TUBE CHASSIS:** Minimum total weight is 3,000 lbs. 55% Left

**ANY 602 / 603 CRATE ENGINE with GM Seals Only And All CFS NON Crate 2 Barrel Engine Rule Will be assessed a 50 lb. Penalty:**

**ALL WEIGHTS WILL BE MONITORED BY TRACK OFFICIALS, AND ARE SUBJECT TO CHANGE ON A GROUP OR INDIVIDUAL BASIS, TO HELP EQUAL OUT THE COMPETITION.**

3. Cars will be at weight before any race. A 1 lb. per green flag lap will be allowed at the end of any race

### **ENGINES:**

#### **ENGINE LOCATION:**

1. Engine **MUST** be centered in chassis.
2. Crankshaft height to be no less than 10" center height to ground.
3. #1 spark plug must be in front of upper ball joint center line.
4. Cars with engine #1 spark plug setback more than 1/2", will be assessed a 100 lb. weight penalty.

### **BLOCK:**

**There will be a 50 lb penalty for this engine option as stated in the weight rules section.**

1. Maximum bore size: 4.060
2. No 400 or aftermarket blocks allowed.

### **CRANKSHAFT:**

1. OEM production stock or Scat replacement, steel 9000 series crankshaft numbers 9-10525 or 9-10442.
2. Normal balancing allowed.
3. No machining other than what is listed allowed.
4. Journals may be polished.
5. Maximum journal size is 2.100, minimum journal size is 2.070.
6. Maximum stroke allowed is 3.493, minimum stroke allowed is 3.480.
7. No knife edging is allowed.
8. Minimum crankshaft weight is 46 lbs.

### **CONNECTING RODS:**

1. Any bushed or non-bushed 5.7 magnetic steel OEM, or aftermarket connecting rods allowed.
2. No aluminum or titanium rods allowed.

#### **PISTONS:**

1. Flat top pistons only.

#### **OIL PANS:**

1. Racing type wet sump oil pans with no external oil pumps are allowed.

#### **CYLINDER HEADS:**

1. Casting numbers must document that the casting used is a minimum of 70 c.c.'s.
2. No modifications to castings of less than 70 c.c.'s to meet 70 c.c.'s allowed.
3. The only heads allowed are (out of box) 70 c.c.'s or more are OEM stock cast iron production heads.
4. World Products Inc. heads, parts # 12250, stock (out of box) permitted. Will be penalized 50 lbs if you use this head.
5. No bowtie, angle plug, turbo, vortec, or any other aftermarket heads allowed.
6. All heads may be milled to a minimum of 70 c.c.'s, machined for screw in studs, guide plates, and drilled for push rod guide holes. **NO GRINDING, PEENING, DRILLING, BEADING, ACID DIPPING, HONING OR SALTING, anything else you can think of.**
7. Valve guides may be replaced, but, must be left at correct OEM height in all ports.
8. All valve guides and valves must be correct angle for castings used.
9. Any valve seals allowed.
10. Maximum O.D. valve springs allowed is 1.250.
11. All valve spring retainers must be magnetic steel.
12. The largest intake valve is 2.02.
13. The largest exhaust valve size is 1.60.
14. No titanium or lightweight valves allowed.

#### **WORK ALLOWED ON THE VALVE SEAT IS AS FOLLOWS:**

1. Multi angle valve job allowed.
2. Metal removal or enlarging of the ports below the top of the valve seat may not be greater than .250 from the top of the valve seat, to the top of the gauge in the intake valve port of the head, and ,125 from the top of the gauge in the exhaust valve port side of the head.

3. Measurements will be strictly enforced by the use of the CFS no-go gauge.
4. Exhaust 1.350 of gauge on exhaust.
5. Intake 1.718 of gauge on intake.

**ANY HEAD MAY BE CONFISCATED IF IT DOES NOT MEET TECH APPROVAL. IF AN OUTSIDE SOURCE IS NEEDED FOR A SECOND OPINION, IT WILL BE TAKEN TO THE FACILITY WITH TWO MEMBERS FROM THE RACE TEAM, AND A TECH OFFICIAL. AT THAT POINT IN TIME, WHETHER THE HEAD IS DEEMED LEGAL OR ILLEGAL, IT WILL BE RETURNED TO THE COMPETITOR, AND ANY PENALTIES WILL BE ASSESSED.**

#### **CAMSHAFT:**

1. Maximum cam lift is .460.
2. Will be measured at valve spring retainer with the rocker arm at the valve.
3. 1.5 rocker arms only.
4. Roller rocker arms are allowed.

#### **CARBURETOR:**

1. Holley 4412 two barrel.
2. The only modification to the carburetor will be the removal of the choke plate and shaft, and jets.
3. Any 1" spacer allowed.
4. No Demon carburetor.

#### **INTAKE:**

1. Factory cast iron or the following Edelbrock performers are permitted.  
Chevrolet #2101  
Ford #2181  
Chrysler #2176
2. No porting, gasket matching, polishing or modifications allowed.

#### **IGNITION:**

1. Only stock type ignition allowed.

#### **RADIATOR:**

1. Any stock or aluminum aftermarket radiator allowed.
2. 1 quart overflow tank required.

**COOLANT:**

1. Positively No Anti-Freeze/Engine Coolant or other glycol based liquids allowed. Water and only red approved water-wetters allowed. No green. Any driver found using such fluids will be subject to a \$250 fine.

**EXHAUST:**

1. Headers permitted.
2. Exhaust pipe size not to exceed 3.5" in outside diameter.
3. Exhaust must exit behind driver compartment, and exit under the car, facing rearward or downward, NOT OUT THE SIDE! Any vehicle having the exhaust exit out the side will have one meet which includes only their initial night to comply. After that initial night they will NOT BE ALLOWED TO COMPETE!
4. Mufflers are mandatory, and must pass a 96 decibel test.

**AIR CLEANER:**

1. K&N and Flow control type are allowed.
2. Air Cleaner only may exit through the hood

**CRATE ENGINE RULES: PAGE #1**

**ALL GM CRATE ENGINES MUST BE SEALED BY ONE OF THE FOLLOWING APPROVED SEALERS. If YOUR CRATE ENGINE HAS ONLY THE GM SEALS YOU WILL BE ASSECED A 50 LB PENALTY . ANY ENGINE IS SUBJECT TO TEAR DOWN AT TECH OFFICIALS DISCRETION.**

## **ACCEPTABLE ENGINE SEALERS AND ACT ACCEPTABLE SEALERS**

1. RPM
2. BUTLER / MCMASTER
3. NATS

CFS reserves the right to take any engine to engine builder if deemed necessary. Two crewmembers and a minimum of one CFS Tech official will be there for the unsealing of the motor. If the motor is found out of specs, than it will be the responsibility of the race team to pay all fees pertaining to the teardown. If the motor is found to be within all GM crate motor specs as stated in the GM Crate Engine manual, than the fees to replace seals will be paid by the Speedway, up to \$\$\$\$ which will be determined after conferring with all approved engine builders in the very near future.

### **CRATE ENGINES:**

1. GM CRATE #88958602 AND #88958603 or any other part number approved and sealed by above authorized engine sealers will be allowed to compete.

#### **Crate Engine #88958602**

2. All approved GM part number 88958602 sealed engines will be allowed to run one 4 barrel Holley carburetor, part #80541-1. No other 4 barrel carburetors or part numbers allowed. No Demon carbs
3. The Holley carburetor, part #80541-1 must be stock out of the box.
4. No changing of base plate.
5. No billet or aftermarket metering blocks allowed.

#### **Crate Engine #88958603**

6. All Approved GM part number 88958603 sealed engines will run 1 single 2 barrel Holley #4412
7. The only modifications allowed are removal of choke plate and shaft.
8. Only allowed carburetor spacers allowed: Canton #85060 & Moroso #64964 (aluminum) Note: These spacers are identical and there should be no difference in performance. No stacking of gaskets.
9. Only GM, HEI stock appearing distributor is allowed.

## **PENALTIES:**

The discretion of the tech department in all matters concerning these rules will be final, and in all cases, all penalties will be determined on a case by case basis by the Contest Board.

## **TRANSMISSIONS & REAR-ENDS:**

1. Any stock 3 or 4 speed manual or automatic transmissions allowed.
2. Clutch, flywheel and torque converter must remain stock.
3. No aluminum flywheels allowed.
4. Minimum 10" clutch disc allowed.
5. The combination of the flywheel, clutch disc and pressure plate must weigh a minimum of 30 lbs.
6. 2" inspection hole is mandatory so flywheel and clutch assembly may be inspected visually.
7. Any rear-end allowed.
8. No lockers or gold tracks, etc.
9. Spools must be solid.
10. Aluminum axle tubes allowed.
11. Rear-end must not have or use any electronic devices.
12. Magnetic Steel Drive shaft only must be painted white No aluminum drive shafts allowed

## **TIRES & WHEELS:**

1. Track tire only. MUST be purchased at track.
2. **8" GOODYEAR tire will be used for 2012 (same as late model) Tire purchasing limitations will set by cfs. American racer tire #704 will also be allowed to compete.**
3. No tire treatments allowed.
4. Tires must meet durometer rule set by Tech.
5. Racing wheels allowed. Maximum 8".
6. 1" steel lugnuts are mandatory.
7. Maximum tread width is 66", measured from center to center, front and rear.

## **SUSPENSION:**

1. Racing springs allowed.
2. springs must be 4" or larger in diameter.
3. Adjustable spring buckets and rear leaf spring shackles allowed.
4. Front and rear jacking bolts are permitted.
5. Tubular upper and lower A-arms are allowed.
6. Aftermarket tie rods and heim joints are permitted.
7. Any sway bar allowed.
8. Rebuildable shocks allowed. MAXIMUM RETAIL PRICE IS \$120 / SHOCK!
9. Shocks may be relocated, yet must be safely mounted and approved by Tech.
10. Only one shock per wheel allowed.
11. Cars must have all four brakes in working order.
12. Cast iron, single piston calipers only.
13. Spindle must be of magnetic steel No aluminum or composite allowed.

#### **ROLL CAGE & SAFETY REQUIREMENTS:**

1. Minimum size of roll cage tubing is 1 3/4", .095 thick.
2. Minimum four point cage required.
3. All cars must have trunk area sealed.
4. Four curved bars in drivers door and three bars in passenger door are mandatory.
7. A horizontal bar is highly recommended from between the two uprights and the dashboard bar.
8. Seat must be an aluminum racing seat bolted to a steel frame connected to cage in original position. Must have six (6) – 3/8" bolts, grade 8 with washers. One must be in each corner of the seat (2-3" from the outer edge) and two in the headrest.
9. No mounting seat to the floor.
9. A support brace must be installed in the rear of the seat.
10. If battery not mounted in stock position under hood, it must be mounted securely in a safety box that is securely mounted outside of the driver's compartment.
11. All cars must have a safety cut-off switch on dash or drivers right side crossbar. Must be within reach of the driver and accessible to safety crews from both sides of the car.
12. All cars must be equipped with a minimum five (5) point harness system.
13. Maximum allowable age for belts is three (3) years.
14. Belts are not legal without date tags.
15. All vehicles must be equipped with an approved window screen, equipped with a quick release device. No string nets allowed. An arrow showing the location of the release must be painted on the outer roof panel.
16. A working fire extinguisher with a working sight gauge is mandatory. It must be attached within reach of the driver and accessible to the driver while strapped in. It

must be located in the center of the car so that it may be reached by safety officials from both sides of the car. Must be securely mounted with a quick release mounting bracket. Zip ties and duct tape are not allowed.

17. All cars must be equipped with Lexan gas splashguard behind the drivers seat.
18. Original fuel tank must be removed and replaced with a fuel cell.
19. Fuel cell must be enclosed in a 20 gauge steel canister. Fuel cell must be held in place by a minimum of four (4) 1" X 1/8" flat steel straps.
20. Maximum twenty-four (24) gallon fuel cell allowed.
21. Trunk may be cut to fit fuel cell only. Minimum height of fuel cell is 8" from the bottom of the fuel cell to the ground. Fuel cell must be centered between frame rails. 1" square tubing holding frame is mandatory. Minimum 1/8" thick, 1" wide steel straps are mandatory, minimum of two straps going in each direction.
22. Minimum 1 3/4" protector bar in back of fuel cell is mandatory.
23. All fuel lines passing through the interior of racecar must be enclosed in steel conduit.
24. All fuel cell vent lines must have a check valve.
25. Center of steering wheel must be padded.
27. All roll bars within drivers reach must be padded.
28. Full firesuits are required. Tech Officials may require you to replace your firesuit if it is full of holes or covered in oil and/or grease.
29. Racing helmets must be DOT or SNELL approved.
30. The following safety items are highly recommended: Full faced helmet or goggles. fire retardant shoes, socks and undergarments. Foam neck braces, Hans or Hutchens devices are highly recommended.
31. Gloves are MANDATORY!!!
32. TWO-WAY RADIOS ALLOWED. If no two-way radios, a scanner is mandatory.
33. **one 5" mirror only will be allowed on drivers post**

### **NUMBERS & PAINT SCHEMES:**

1. All cars must be neat appearing, painted in contrasting colors.
2. Lettering will be neatly done. No Profanity allowed!
3. Numbers will be at least 18" high. There must be numbers on each side of the racecar. There must be a number on the roof, lettered to be readable by scorers on right hand side of the racecar. There must be a 4" number on the upper left passenger side of the windshield, a 4" number on the right front headlight cover, and a 4" number on the right rear tail light cover.
4. The head scorer reserves the right to ask race teams to make their numbers more legible. You will have one week to comply. Failure to comply will result in your car not being scored.

## **DRIVER ELIGIBILITY:**

- 1. Age limitations will be at the discretion of CFS and must meet CFS criteria to compete.**
- 2. All drivers must be willing to submit to an alco-sensor test if deemed necessary by Track Officials. Failure to submit to test meets automatic license suspension and immediate removal from Speedway grounds.**
- 3. All rules are subject to change by the Director of Competition. It is the responsibility of the competitor to obtain and become familiar with the rules pertaining to the division he/she competes in along with General Rules and written race procedures. If there are any major changes in the rules, a memo will be mailed to each competitor. You will be expected to comply by the next race date, or the date mandated in the memo. It will also be updated on our website.**
- 4. When you sign your license application, you have signed that you understand the rules and will abide by them.**
- 5. The rules and/or regulations set forth herein, are designed to provide for the orderly conduct of racing events, and to establish a minimum acceptable requirements for such events. These rules are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator or an Official. All rules clarifications are void from the previous seasons, and cannot be used in the 2012 season at CFS.**
- 6. In the case of failure to pass tech due to presumable on track damage it will be up to the car crew to prove and at the discretion of tech weather the car will or will not pass tech due to on track damage.**

**ANYTHING NOT MENTIONED IN THESE RULES SHALL REMAIN OEM STOCK FOR MAKE OF VEHICLE USED UNLESS APPROVED BY TECH. IF IT DOESN'T SAY IT IN BLACK AND WHITE, DO NOT DO IT!!!!**

## **PENALTIES:**

**The discretion of the tech department in all matters concerning these rules will be final, and in all cases, all penalties will be determined on a case by case basis by the Contest Board.**

***All Tech Dicisions are Final. The Tech Team Reserves the Right to Make any***

***Changes that Need to be Made for the Best Interest of Competition.***

***page 3***

**NEW 2012 PURSE: 12 Cars or more      2010 Purse 11 cars or less**

<b>1<sup>st</sup></b>	<b>\$400</b>	<b>1</b>	<b>\$300</b>
<b>2<sup>nd</sup></b>	<b>\$300</b>	<b>2</b>	<b>\$225</b>
<b>3<sup>rd</sup></b>	<b>\$200</b>	<b>3</b>	<b>\$150</b>
<b>4<sup>th</sup></b>	<b>\$150</b>	<b>4</b>	<b>\$125</b>
<b>5<sup>th</sup></b>	<b>\$125</b>	<b>5</b>	<b>\$100</b>
<b>6<sup>th</sup></b>	<b>\$100</b>	<b>6</b>	<b>\$ 90</b>
<b>7<sup>th</sup></b>	<b>\$ 90</b>	<b>7</b>	<b>\$ 80</b>
<b>8<sup>th</sup></b>	<b>\$ 80</b>	<b>8</b>	<b>\$ 70</b>
<b>9<sup>th</sup></b>	<b>\$ 60</b>	<b>9</b>	<b>\$ 60</b>
<b>10<sup>th</sup></b>	<b>\$ 50</b>	<b>10</b>	<b>\$50</b>
<b>11-24<sup>th</sup></b>	<b>\$ 30</b>	<b>11</b>	<b>\$35</b>